

# ZHENYANG LIGHTING TECHNOLOGY CO.,LTD

---

## SPECIFICATION

Product Name: LED RGB FLOOD Light

---





#### ADVANTAGE:

- ◆ >120-140m/w
- ◆ Epistar LED
- ◆ RGB Radio frequency,Control distance 15-20M
- ◆ High power efficiency outdoor driver
- ◆ Die -casting aluminum housing
- ◆ Lens reflector improves light efficiency
- ◆ SUS304 Stainless steel screw
- ◆ IP66 Waterproof grade
- ◆ 5 years warranty

#### APPLICATION:

- ◆ Warehouse, factory and workshops;
- ◆ Sports fields, Airport, Large Construction sites, ;
- ◆ Exhibition hall, Golf courts, Gymnasium and supermarkets, etc.

**TECHNICAL DATA SHEET****Product Specifications**

Electrical Parameters	Input Voltage	AC100-277V	CCT	2700-6500K
	Material	Aluminum Alloy	Driver	Zhihe
	LED Type	Epistar	Lamp Initial Flux	110-140 lm/W
	Working Life	50000 hours	Power Factor	>0.95
	CRI	> 80	Beam Angel	120°
	Function	RGB Radio frequency	Control Distance	15-20M
	IP Grade	IP66	Operating Temperature	-30°C ~45°C
Model	LED Power	LED Quantity	Product Size (MM)	Product Weight (KG)
ZY-FL10-R	10W	18pcs	129*99*44	0.52
ZY-FL20-R	20W	36pcs	175*135*44	0.90
ZY-FL30-R	30W	60pcs	215*175*47	1.3
ZY-FL50-R	50W	90pcs	275*225*48	2.1
ZY-FL100-R	100W	180pcs	325*275*53	3.5

**PACKAGE**

Model	Carton Packing			
	Net Weight of Carton(KG)	Gross Weight of Carton(KG)	Size of Carton (MM)	Box PCS /Carton
ZY-FL10-R	15.6	17.5	560*370*170	30PCS
ZY-FL20-R	18	19	590*330*210	20PCS
ZY-FL30-R	19.5	20.5	440*400*250	15PCS
ZY-FL50-R	21	23	510*360*310	10PCS
ZY-FL100-R	17.5	18.5	38*31.5*39	5PCS